

# **Declaration of conformity**

on plastic materials and articles intended to come into contact with food

We declare under our sole responsibility that our products:

Graduated cylinders SAN, tall form, with raised scale,

item no. 64891, 6491, 65091, 65191, 65291

meet the present requirements of the Ordinance on Materials and Articles and Regulation (EC) No 1935/2004<sup>[1]</sup> and Commission Regulation (EU) Nr.10/2011<sup>[2]</sup> in their actual version (inclusive of their amendments), too.

Analyses by an independent, accredited laboratory according to the overall migration limit of the final article validates no overstepping of the regulated limits. Also, during the organoleptic tests no negative interaction with the food (change of taste and odor of the food) could be discovered. The testing has been performed according to article 17 and 18 of Commission Regulation (EU) No 10/2011 in conjunction with Annex V. Therefore, the abovenamed products comply with the requirements of Commission Regulation (EU) No. 10/2011 and could be used related to the specified limitation of migration limits in contact with food.

According to statements provided by our raw materials supplier we could declare, that the material currently used for production of the above-named products, has been manufactured in accordance with the relevant requirements of good manufacturing practice for articles intended to come into contact with food, according to Commission Regulation (EC) No 2023/2006<sup>[3]</sup>.

Unless the raw material used for the production of the above-named products contains substances with specified limitation (SML / QM) the defined limiting values according to Commission Regulation (EU) No 10/2011 were observed. The actual version of the Commission Regulation can be downloaded from the Internet at <a href="http://eurlex.europa.eu">http://eurlex.europa.eu</a> or <a href="http://bfr.bund.de">http://bfr.bund.de</a>.

 $^{[1]}$  OJ L 338, 13.11.2004, p. 4–17

<sup>[2]</sup> OJ L 12, 15.1.2011, p. 1–89

<sup>[3]</sup> OJ L 384, 29.12.2006, p. 75–78



Rev. 10 - 11.02.2025



# 1. Specification for envisaged use or limitations:

- Kind of food, which could come into contact with the used material:

All types of food (dry, aqueous, sour, fatty) except alcoholic beverages - testet according to table 3 annex III with listed food simulants (1. distilled water or water of equivalent quality or food simulant A (Ethanol 10 Vol.-%); 2. food simulant B (Acetic acid 3 Gew.-%); and 3. food simulant D2 (Any vegetable oil with less than 1 % unsaponifiable matter) - with 95% ethanol and isooctane alternatively according to annex V, chapter 2 paragraph 2.1.3 Conditions of contact when using food simulants.).

- Kind of food, which should not come into contact with the used material:
  - alcoholic beverages

### 2. Information on the intended field of application:

- Contact time and contact temperature for using and storing food:

The applied testing conditions relate to short-term hot contact for a maximum of 30 minutes not exceeting 70 °C. This also includes a shorter contact as well as contact at lower temperatures.

#### 3. Research results:

3.1. Organoleptic test (triangle test, 6 persons) according DIN EN 10955:2004-06

**Test conditions:** 

Type of contact: Insert

**Used simulant:** Mineral water after 0,5 h at 40 °C

	Intensity	Significance	Limiting value <sup>[4]</sup>	Assessment
Deterioration of smell	0	> 20 %	max. 2.5	passed
Deterioration of taste	1,0	> 20 %	max. 2.5	passed

Scale of intensity: 0 = imperceptible

1 = just discernible

2 = discernible

3 = clear

4 = strong



# 3.2. Overall migration

#### **Test conditions:**

Type of contact: Filling

Method: DIN EN 1186:2002-07

#### Migration with the following used simulants:

Acetic Acid 3 % for 10 d at 40 °C, with a S:V of 1.2 dm<sup>2</sup>:50 ml

Ethanol 10 % for 10 d at 40 °C, with a S:V of 1.2 dm $^2$ :50 ml

Olive oil for 10 d at 40 °C, with a S:V of 1.0 dm $^2$ :100 ml

Isooctane for 2 d at 20 °C, with a S:V of 1.2 dm<sup>2</sup>:50 ml

permitted limit value: max. 10,0 mg/dm<sup>2</sup> [5].

Simulant	Unit	Measurement -uncertainty	Sample	1. Contact	2. Contact	3. Contact = Measured value	Assessment
Acetic Acid 3 %	mg/dm²	10 %	1.	< 1	< 1	< 1	passed
			2.	< 1	< 1	< 1	passed
			3.	< 1	< 1	< 1	passed
	mg/dm²	10 %	1.	< 1	< 1	< 1	passed
Ethanol 10 %			2.	< 1	< 1	<1	passed
			3.	< 1	< 1	< 1	passed
	mg/dm²	30 %	1.	< 5.4	< 4.5	< 4.0	passed
Olive oil			2.	< 6.9	< 6.5	< 6.3	passed
			3.	< 3.7	< 3.4	< 3.2	passed
	mg/dm²	30 %	1.	< 1	< 1	< 1	passed
Isooctane			2.	< 1	< 1	<1	passed
			3.	< 1	< 1	< 1	passed
	mg/dm²	dm² 30 %	1.	< 1	< 1	< 1	passed
Ethanol 95 %			2.	< 1	< 1	< 1	passed
			3.	< 1	< 1	< 1	passed

According to Article 12 of Regulation (EU) No. 10/2011 plastic materials and articles shall not transfer their constituents to food simulants in quantities exceeding 10 milligrams of total constituents released per  $dm^2$  of food contact surface ( $mg/dm^2$ ). With regard to manner and extent of the performed overall migration test the limiting value is met by the present sample.



# 3.3. Specific Migration

### 3.3.1. Metalls

**Test conditions:** 

Type of contact: Filling

Method: DIN EN ISO 17294-2:2014-01

**Used simulant:** Acetic Acid 3 % for 10 d at 60 °C, with a S:V of 1.2 dm<sup>2</sup>:50 ml

Parameter	Limiting value <sup>[5]</sup> :	Unit	1. Contact *	2. Contact *	3. Contact* =  Measured value	Assessment:
Aluminium [5]	≤1.0	mg/kg	< 0.1	< 0.1	< 0.1	passed
Antimony <sup>[8]</sup>	≤0.04	mg/kg	< 0.01	< 0.01	< 0.01	passed
Arsenic <sup>[8]</sup>	≤0.01	mg/kg	< 0.002	< 0.002	< 0.002	passed
Barium <sup>[6]</sup>	≤1.0	mg/kg	< 0.01	< 0.01	< 0.01	passed
Lead <sup>[8]</sup>	≤0.01	mg/kg	< 0.002	< 0.002	< 0.002	passed
Cadmium <sup>[8]</sup>	≤0.002	mg/kg	< 0.001	< 0.001	< 0.001	passed
Chromium [8]	≤0.01	mg/kg	< 0.01	< 0.01	< 0.01	passed
Cobalt [6]	≤0.05	mg/kg	< 0.01	< 0.01	< 0.01	passed
Iron <sup>[6]</sup>	≤48.0	mg/kg	< 0.1	< 0.1	< 0.1	passed
Copper <sup>[6]</sup>	≤5.0	mg/kg	< 0.01	< 0.01	< 0.01	passed
Lithium <sup>[6]</sup>	≤0.6	mg/kg	< 0.01	< 0.01	< 0.01	passed
Manganese [6]	≤0.6	mg/kg	< 0.01	< 0.01	< 0.01	passed
Nickel <sup>[7]</sup>	≤0.02	mg/kg	< 0.01	< 0.01	< 0.01	passed
Mercury <sup>[8]</sup>	≤0.01	mg/kg	< 0.001	< 0.001	< 0.001	passed
Zinc <sup>[5]</sup>	≤5.0	mg/kg	< 0.05	< 0.05	< 0.05	passed
Europium <sup>[8]</sup>		mg/kg	< 0.01	< 0.01	< 0.01	passed
Gadolinium <sup>[8]</sup>	≤0.05	mg/kg	< 0.01	< 0.01	< 0.01	passed
Lanthanum <sup>[8]</sup>		mg/kg	< 0.01	< 0.01	< 0.01	passed
Terbium <sup>[8]</sup>		mg/kg	< 0.01	< 0.01	< 0.01	passed

<sup>\*</sup> relative measurement uncertainty 30 %

<sup>&</sup>lt;sup>[6]</sup> according to Regulation (EU) No 10/2011 - OJ L 12, 15.1.2011, p. 1–89

 $<sup>^{[7]}</sup>$  according to Regulation (EU) No 10/2011 adapted by Regulation (EU) 2017/752 - OJ L 113, 29.4.2017, p. 18–23

<sup>[8]</sup> according to Regulation (EU) No 10/2011 adapted by Regulation (EU) 2020/1245 - OJ L 288, 03.9.2020, S. 1–19



According to information provided by our raw material supplier no monomers or additives are used, which are controlled by a specific migration limit:

# 3.3.2. Acrylnitrile [FCM 225; Ref.-no. 12100]

**Test conditions:** 

Type of Contact: Filling

Method: CEN/TS 13130-3:2004

**Used Simulant:** Olive oil for 10 d at 60 °C, with a S:V of 1.2 dm<sup>2</sup>:50 ml

Limiting value [5]:	imiting value <sup>[5]</sup> : Unit		2. Contact *	3. Contact * = Measured value	Assessment:
0.01	mg/kg	< 0.01	< 0.01	< 0.01	erfüllt

<sup>\*</sup> relative measurement uncertainty 30 %



# 3.4. GC-MS-Overview analysis (NIAS<sup>[6]</sup> - screening) according to EPA Method 8270D:

**Test conditions:** 

Type of Contact: Insert

Method: EPA 8270D (GC-MS)

Used Simulant: Ethanol 95 % for 10 d at 60 °C, with a S:V of 2.4 dm<sup>2</sup>:100 ml

The migrate was analyzed gas chromatographically by means of mass spectrometric detection. For the identification of the signals in the chromatogram a commercial mass spectra library was used. Results are expressed in hexadecane (SVOCs) equivalents and may vary to the real amount. We point out that the mentioned amounts may vary to the real amounts as this is a screening approach.

Non-volatile substancen (SVOCs):			
Substance	CAS	Concentration# [mg/kg]	
Aliphatic hydrocarbons (C6-C12) ( <b>Sum</b> ) (1)	-	11.42	
Aliphatic hydrocarbons (C12+) ( <b>Sum</b> ) (1)	-	-,-	
2-[1-(4-Cyano- 1,2,3,4- tetrahydronaphtyl)]propannitril (4)***	57964-39-3	0.02	
Not identified compounds containing aromatic ring(2)	-	0.06	
Not identified organic acid ester (3)	-	0.02	

<sup>\*</sup>Measurement uncertainty 65% (the repeatability within a measurement series of a sample (same substance) < 10%)

<sup>\*\*\*</sup> Cramer-Class III: Limiting value: (sTDI) of 0,0015 mg/kg b.w./ day resulting in a derived SML value of 0,09 mg/kg foodstuff



# Assessment of NIAS<sup>[6]</sup> screening results

### Aliphatic hydrocarbons (1)

Aliphatic hydrocarbons were detected during the investigation. Currently, no assessment values for the migration of hydrocarbons exist within the framework of Regulation (EU) 10/2011. As the sample at hand is made of polyolefin plastic, it is possible that the hydrocarbons originate from the plastic material itself.

### Not identified compounds (2)

According to the type and scope of the investigations carried out, compounds that were not clearly identified were recorded. Since no clear identification is possible based on the mass spectrum, a final evaluation cannot be made at this point.

#### Fatty acid, -esters, -amides (3)

According to the type and extent of the investigations carried out, fatty acid derivatives were detected. According to Regulation (EU) No 10/2011 Annex I, the derivatives detected here (from animal or vegetable oils) with linear or branched, monohydric, primary, saturated, aliphatic alcohols (C 1-C 22) and the amides detected here are listed without a specific migration limit. In view of this, the content recorded here is judged to be inconspicuous.

### Other substances (4)

According to the type and scope of the investigation carried out, further substances were detected that are not listed in Annex I of Regulation (EU) No. 10/2011. SAN trimers are mixtures of isomers formed by condensation of two molecules of acetonitrile and one molecule of styrene and can be formed as by-products during polymer production.

The toxicology of SAN trimers is discussed in the scientific literature. Investigations within the framework of the American NTP Technical Report revealed, among other things, DNA damage in brain and liver cells with oral administration as well as changes in the peripheral nervous system. With regard to the investigations carried out within the framework of this study, there are inconclusive results of in vitro genotoxicity. There is no sufficient evidence for carcinogenic activity (NTP Technical Report on the toxicoloy and Carcinogenesis study of styrene-Acrylonitrile Trimer; National Toxicology Program).



Due to the contradictory data on toxicology, the limit value of <0.01 mg/kg, not detectable in the sense of Regulation (EU) No. 10/2011, should be guiding. This limit value is not complied with in the study carried out. In addition, Article 19 of Regulation (EU) No 10/2011 provides, that substances that have been detected and are not included in Annex I to the Union list must be subject to a risk assessment in accordance with scientifically recognised principles.

Migration limits for the detected substance do not exist at present, toxicological studies on this substance are also not available to us. We are therefore guided by the classification of substances into Cramer classes based on structural properties. This was done according to the "Threshold of Toxicological Concern" (TTC) concept using the software "Toxtree 3.1.0, Revised Cramer Decision Tree".

The underlying structure of 2-[1-(4-Cyano- 1,2,3,4- tetrahydronaphtyl)] propannitrile, leads to a classification of Cramer Class I, for which an intake of up to 1,5  $\mu$ g/kg body weight/day is considered tolerable. Assuming a person weighing 60 kg, this corresponds to a permitted limiting value of 90  $\mu$ g substance/person per day.

Considering all substances, for which a classification into a Cramer class is given, considering the different hazard classes, a daily consumption of 1 kg of food, that has been in contact with the article under similar conditions and has comparable dissolving properties with regard to the substances, will not exceed the limiting values and therefore the content of the other detected substances can be regarded as inconspicuous.



# 4. Reference to "Dual-Use-Substances":

The raw material do not contain substances also authorised as direct food additives ("Dual use additives") according to Regulation (EG) No  $1333/2008^{[9]}$  in its actual version.

### No functional barrier of plastic material is used.

To ensure the traceability of the product according to Regulation (EC) No 1935/2004 a date-stamp is used at the product itself or a LOT No. is printed on the product label.

In addition, we have to point out that the used raw material is not intended to be used for medical, pharmaceutical or healthcare applications and the manufacturer do not support their use for such applications. This product is neither tested nor represented as suitable for medical or pharmaceutical uses by us. It is in the scope of the enduser to validate the product for applications which differs from the guidelines of the Commission Regulation (EU) No 10/2011.

VITLAB GmbH

Grossostheim, 11. February 2025

Wolfgang Nicolaus i.A. Dr. Stephan Schmidt

Geschäftsführer Beauftragter Product Compliance

Managing Director Regulatory Affairs

This letter has been typed and is valid without signature.